

保安型系類 / Safety Type

| UL 810 認證 容許故障電流10,000A / 保安等級 P2 | | UL 810 approval with AFC 10,000A and Safety class P2 | | |
|---|-------------------|---|---|--|
| 圖片 Pictures | 型式 Model | 用途 Application | 特點 Features | 認證 Certificate |
|  | SCA SCB SCE | 馬達啓動兼運轉 照明器具 電力電子設備 Motor running, Lighting, Power electronic equipment | 方形，UL引線，防火塑殼，防火樹脂充填。SCB型：外殼附固定片。SCE型：外殼附固定腳。 Box style, UL leads, Fire-retardant plastic case, Fire-retardant epoxy resin filling. Type SCB: case with mounting tab Type SCE: case with integral mounting tab |   |
|  | SFA SFB SFE | | 方形，快速插接端子，防火塑殼，防火樹脂充填。SFB型：外殼附固定片。SFE型：外殼附固定腳。 Box style, Quick-connect terminals, Fire-retardant plastic case, Fire-retardant epoxy resin filling. Type SFB: case with mounting tab Type SFE: case with integral mounting tab | |
|  | SWA | | 方形，鍍錫裸銅線，防火塑殼，防火樹脂充填。 Box style, Tinned copper wires, Fire-retardant plastic case, Fire-retardant epoxy resin filling. | |
|  | YFP | | 圓形，快速插接端子，鋁質外殼，內附保安裝置。 Round style, Quick-connect terminals, Aluminum case, Internal protective device. | |
|  | YFP+B | | 圓形，快速插接端子，鋁質外殼，內附保安裝置。外殼底有附固定用螺絲。 Round style, Quick-connect terminals, Aluminum case, Internal protective device, Case with mounting stud on the bottom. | |
|  | RFP | | 橢圓形，快速插接端子，鋁質外殼，內附保安裝置。 Oval style, Quick-connect terminals, Aluminum case, Internal protective device. | |
|  | RBC | | 圓形，四線插接式端子蓋內附放電電阻，鋁殼附絕緣膜。 Round style, four-way wire-grip connector with internal discharge resistor, Aluminum case with PVC tube. | |