


附件(Dimension):



外型尺寸(Dimension):

| 型式 (TYPE) | 額定電流 (Current Rating) | A | B | C | D | E | F | G |
|--------------|--------------------------|----|------|-------|------------------|------------------|--------------------|-----|
| MDA-B1F | 100AMPS | 31 | 27.3 | 188.7 | $\varnothing 30$ | $\varnothing 28$ | $\varnothing 16.1$ | 250 |

附註(Notes): 本型式產品不含熔絲鏈，請另選購。

The products Do Not include fuse links, which are selected by users.

熔絲鏈容量選定為電容器額定電流之1.65~2.5倍，K-type快速型。

The current rating of type-K(fast) fuse link should be selected on 1.65~2.5 times of rated current of capacitor.

電器特性(Electrical Ratings):

| 最大額定電壓 (Max Voltage Rating) | 熔絲鏈最大額定電流 (Max. fuse link size) |
|--------------------------------|------------------------------------|
| 15kV | 100AMPS |

發行日期:2020.08.10

| | | |
|--|---------------|------|
| 圖名: 電容器彈力熔絲組 Capacitor Expulsion Fuse Unit (TYPE: MDA-B1F) 裕昌機電工廠股份有限公司 YUHCHANG ELECTRIC CO., LTD. 台中市清水區中正街五十九號 | 圖號 MDA-B1F | |
| | 版次 | 01 |
| | A 4 | 第三角法 |
| | 比例 | |
| | 單位 | MM |